





CONTROL UNIT

Next Gen SOLO PRO+ Control Unit

- 10" Sunlight Viewable Touchscreen Screen
- New and Improved User Interface
- Designed to meet IP65 ingress protection standards.
- 8 Dedicated Hot-Keys.
- Optional Dedicated Camera Control Pod
- Ergonomic, Soft-Touch, Waterproof, Anti-Microbial Keyboard
- Embedded Reporting Software with all major reporting standards.
- Weatherproof, Industrial Case



Technical Data

Screen	Display: 10" touchscreen, 1280 x 800 pixels Brightness: 800 nits (sunlight viewable)
Control Pods	0 (upgradeable to 1 for pan-rotate camera control)
Keyboard	TKL silicone-encapsulated backlit keyboard with QWERTY layout. International versions also available.
Battery	Lithium-ion with up to 7.5 hours on screen time.
Charging	112 W USB-C power supply (20 VDC)
Text Overlay	16 page (selectable text and colours)
Reporting Software	Embedded Minicam Reporting Software powered by WinCan ProTouch
File Formats	720 x 594 (PAL) Video: MPEG-4 Images: JPEG
Internal Storage	Approx. 100 GB available
External Memory	Media connectivity via USB-C (side) ports with HDMI support
Connections	1x Minicam Control Interface (rear) 2x USB-C (side) supporting USB 3.0 (top) and USB 2.0 (bottom)
Processor	Intel Atom® x6413E Quad-Core Processor (1.5 GHz)
RAM	4 GB LPDDR4
Language Support	Multiple
Power Consumption	TBC
Dimensions	501 mm x 173 mm x 395 mm (19.5" x 7" x 15.5")
Weight	7 kg (15.5 lbs)
Protection Class	IP65
Operating Temperature	-10 °C ~ +40 °C (+14 °F ~ +104 °F)